

201 Circle Drive N, Suite 116, Piscataway, NJ 08854

Tel: 732-412-6007 ext. 218 • Fax: 732-412-6008 • Web: www.zkaccess.com • Email: sales@zkaccess.com


Price List

Item	Picture	Description	End User Price, FOB, NJ
C3 Access Control Panel Boards			
C3-100		One-door Two-way Controller Card: 30,000 Event Buffer: 100,000 Reader Port: 2ea(26/34bits Weigand, 8bits burst for PIN) Communication: RS485, TCP/IP Input Port: 2ea(1 exit button, 1 door sensor) Output Port: 2ea(1 FORM-C Relay Output for lock, 1 Aux FORM-C Relay Output)	\$300
C3-200		Two-door Two-way Controller Card: 30,000 Event Buffer: 100,000 Reader Port: 2ea (26 / 34 bits Weigand, 8bits burst for PIN) Communication: RS485, TCP/IP Input Port: 6ea (2 exit button, 2 door sensor, 2 Aux Input) Output Port: 4ea(2 FORM-C Relay Output for lock, 2 Aux FORM-C Relay Output)	\$450
C3-400		Four-door One-way Controller Card: 30,000 Event Buffer: 100,000 Reader Port: 4ea (26/34bits Wiegand,8bits burst- PIN) Communication: RS485, TCP/IP Input Port: 12ea (4 exit button, 4 door sensor,4 Aux Input) Output port: 8ea(4 FORM-C Relay Output, 4 Aux FORM-C Relay Output)	\$550
C3 Access Control Panel Bundles			
C3-100 Bundle		A package of C3-100 including Metal box and PSU(Power Supply Unit) C3-100 + Power Supply + Case Gross Weight: 7.37 lbs. (3.35kg) Package Size: 380(L)*80(H)*290(W)mm	\$430
C3-200 Bundle		A package of C3-200 including Metal box and PSU(Power Supply Unit) C3-200 + Power Supply(ZKPSM030B) + Case Gross Weight: 7.4 lbs. (3.4kg) Package Size: 380(L)*80(H)*290(W)mm	\$580
C3-400 Bundle		A package of C3-400 including Metal box and PSU(Power Supply Unit) C3-400 + Power Supply(ZKPSM030B) + Case Gross Weight: 7.5 lbs. (3.55kg) Package Size: 380(L)*80(H)*290(W)mm	\$680



			
C3 Demo Kit		C3 Demo Kit Integrated 12V DC Power supply, K1-1 Exit switch, 2 nos. of KR100 card readers, ZKABK Exit switch, ZKACCESS software	\$350
inBio Access Control Panel Boards			
inBIO160		One-door Two-way Controller Fingerprint: 3000 Card:30,000 Event Buffer:100,000 Reader Port:2ea (Weigand and RS485 connect 2 FP readers) Communication: RS485, TCP/IP	\$560
inBIO260		Two-door One-way Controller Fingerprint: 3000 Card:30,000 Event Buffer:100,000 Reader Port:2ea (Weigand and RS485 connect 2 FP readers) Communication: RS485, TCP/IP	\$880
inBIO460		Four-door One-way Controller Fingerprint: 3000 Card:30,000 Event Buffer:100,000 Reader Port:2ea (Weigand and RS485 connect 2 FP readers) Communication: RS485, TCP/IP	\$1,200
inBio Access Control Panel Bundles			
inBIO160 Bundle		A package of inBIO160 including Metal box and PSU(Power Supply Unit) inBio160 + Power Supply + Case Gross Weight: 7.37 lbs. (3.35kg) Package Size: 380(L)*80(H)*290(W)mm	\$690
inBIO260 Bundle		A package of inBIO260 including Metal box and PSU(Power Supply Unit) inBio260 + Power Supply + Case Gross Weight: 7.37 lbs. (3.35kg) Package Size: 380(L)*80(H)*290(W)mm	\$1,010
inBIO460 Bundle		A package of inBIO460 including Metal box and PSU(Power Supply Unit) inBio460 + Power Supply + Case Gross Weight: 7.37 lbs. (3.35kg) Package Size: 380(L)*80(H)*290(W)mm	\$1,330
FR1200		Slave Fingerprint Reader Communication: RS485 with inBIO controller or Standalone Biometric Reader Controllers DIP switch for RS485 address	\$198
		Slave Fingerprint Reader Necessary for enrollment with inBio	

ZK4000		Communication: RS485 with inBIO controller or Standalone Biometric Reader Controllers DIP switch for RS485 address	\$80
inBio Demo Kit		inBio Demo Kit Demo kit includes: inBio-160 panel, Integrated 12V DC Power supply, K1-1 Exit switch, 2 nos. of FR1200 fingerprint readers, ZKABK Exit switch, ZKACCESS software.	\$599

Standalone Biometric and RFID Reader Controllers			
F6		Standalone Biometric Reader Controller Communication: RS485 Fingerprint Capacity: 1000 Logs Capacity: 30000 SD Card Support	\$258
		ID	\$315
		Mifare	\$372
		HID	n/a
F18		Standalone Biometric Reader Controller Communication: RS485, TCP/IP; USB- Host WeigandInput/Output Fingerprint Capacity: 1500 Logs Capacity: 30000	\$718
		ID	\$775
		Mifare	\$832
		HID	n/a
US700		Standalone Biometric Reader Controller Communication: TCP/IP; USB Host 26-bit Weigand Input/Output Fingerprint Capacity: 1500 Logs Capacity: 30000	\$698
		ID	\$755
		Mifare	\$812
		HID	\$869
F707		Standalone Biometric Reader Controller Communication: TCP/IP 26-bit Weigand Output Fingerprint Capacity: 1000 Logs Capacity: 30000	\$678
		ID	n/a
		Mifare	n/a
		HID	n/a
MB700		Standalone Multi-Biometric Reader Controller Communication: TCP/IP 26-bit Weigand Output Fingerprint Capacity: 2000 Face Capacity: 400 Logs Capacity: 10000	\$900
		ID	\$957
		Mifare	\$1,014
		HID	\$1,071
SC403		Standalone RFID Reader Controller Communication: RS232/485 TCP/IP and USB-Host User Capacity: 30000 Card Capacity: 50000	\$318
		ID	\$375
		Mifare	\$432
		HID	\$489
		Waterproof Standalone Biometric Reader Controller Communication: TCP/IP, USB Host	

TF1700		26-bit Weigand Input/Output Fingerprint Capacity: 2200 Card Capacity: 10000 Logs Capacity: 30000	\$850
		ID	\$907
		Mifare	\$964
		HID	n/a

Weigand only Readers			
KR100E		Read 125KHz Proximity ID card number Weigand output 26bit; Single gang Dimension: 116*75*17.3mm	\$40
KR100M		Read 13.56MHz Mifare card number Weigand output 34bit; Single gang Dimension: 116*75*17.3mm	\$50
KR101E		Read 125KHz Proximity ID card number Weigand output 26bit, Mullion mount Dimension: 77.5*42.8*16.5mm	\$40
KR101M		Read 13.56MHz Mifare card number Weigand output 34bit, Mullion mount Dimension: 77.5*42.8*16.5mm	\$50
KR102E*		Read 125KHz Proximity ID card number or PIN Weigand output 26bit Dimension: 86*86*16.3mm	\$44
KR102M*		Read 13.56MHz Mifare card number or PIN Weigand output 34bit Dimension: 86*86*16.3mm	\$54
KR500E		Read 125KHz Proximity ID card number Weigand output 26bit, Mullion mount Dimension: 77.5*42.8*16.5mm	\$40
KR500M*		Read 13.56MHz Mifare card number Weigand output 34bit, Mullion mount Dimension: 77.5*42.8*16.5mm	\$50
KR503E		Read 125KHz Proximity ID card number Weigand output 26bit, Single gang Dimension: 116*75*17.3mm	\$40
KR503M*		Read 13.56MHz Mifare card number Weigand output 34bit, Single gang Dimension: 116*75*17.3mm	\$50
KR502E		Read 125KHz Proximity ID card number Weigand output 26bit, Mullion mount Dimension: 77.5*42.8*16.5mm	\$40
KR502M*		Read 13.56MHz Mifare card number Weigand output 34bit, Mullion mount Dimension: 77.5*42.8*16.5mm	\$50
KR501E		Read 125KHz Proximity ID card number Weigand output 26bit, Mullion mount Dimension: 77.5*42.8*16.5mm	\$40
KR501M*		Read 13.56MHz Mifare card number Weigand output 34bit, Mullion mount Dimension: 77.5*42.8*16.5mm	\$50
* Special order only. Please consider 4-6 weeks delivery.			





Accessories			
Exit Buttons			
K1-1		No touch / Touch Free Exit Sensor (Diffused NO NC) COM relay output	\$42
ZKABK-802		Size: 86L * 86W * 20T (mm)	\$14
ZKABK-800A/B		Size: 800A: 86L * 50W * 20T (mm) 800B: 86L * 86W * 20T (mm)	\$12
Card and Fobs			
Prox Card Thick (Clamshell)		125kHz Prox Cards- Thick (Read only) (Min. Order Quantity- 100 cards)	\$1
Prox Cards Thin (ISO)		125kHz Thin Prox cards- ISO Standard (Read only)	\$1
Key-Fobs		125KHz Key Fobs (Read Only)	\$2
Mifare Card		MF1 S50 Mifare card with 1 Kbyte EEPROM	\$3
Others			
Casing for Controller		Suitable for C3-100/200/400; Weight: Approx. 5 lbs.; Package Size: 345(L)*70(H)*275(W)mm Color: Black	Gross 90.00
CR10E		125kHz Proximity Card reader with USB interface	40.00
CR10M		13.56MHz Mifare Card reader with USB interface	60.00
RS485P Converter		Active RS232-RS485 Converter	130.00
POE Power Over Ethernet		12V DC POE 300mA 95(L)*20(H)*20(W)mm. Color: Silver	80.00

**BL100 Fingerprint
Deadbolt**



BL100 Fingerprint Deadbolt

\$189

Network Video Surveillance System			
ZKIR372 (15m-20m) ZKIR373 (20m-30m) IR Weatherproof Bullet IP Camera		ZKIR372 (15m-20m) & ZKIR373 (20m-30m) * H.264 image compression * 1/3" CMOS sensor * 1280*720 resolution and WDR * 6mm/12mm fixed lens * IP66 * ICR-Cut Filter * Motion detection * Webserver * External audio connections * Alarm contacts & RS 485 Connectivity * 12V power supply included * Micro SD card slot, supports max 32GB	\$530
		ZKIR372-P (POE) / ZKIR373-P (POE)	\$587
		ZKIR372-W (WiFi) / ZKIR373-W (WiFi)	\$587
ZKMD372 (15m-20m) IR Vandal-proof Dome IP Camera		ZKMD372 (15m-20m) * H.264 image compression * 1/3" CMOS sensor * 1280*720 resolution and WDR * 4-9mm varifocal lens * IP66 * ICR-Cut Filter * Motion detection * Webserver * External audio connections * Alarm contacts & RS 485 Connectivity * 12V power supply included * Micro SD card slot, supports max 32GB	\$510
		ZKMD372-P (POE)	\$567
		ZKMD372-W (WiFi)	\$567
ZKMD470 Mini Dome IP Camera		ZKMD470 * H.264 image compression * 1/3" CMOS sensor * 1280*720 resolution and WDR * 6mm fixed lens * Motion detection * Webserver * 12V power supply included * Micro SD Card slot; supports max 32GB * Embedded MIC	\$370
		ZKMD470-P (POE)	\$427
		ZKMD470-W (WiFi)	\$427
ZKIP472 Cube IP Camera		ZKIP472 * H.264 image compression * 1/3" CMOS sensor * 1280*720 resolution and WDR * 6mm fixed lens * ICR-Cut Filter * Embedded IR array LED * Motion detection * Webserver * 12V power supply included * Micro SD Card slot; supports max 32GB * Embedded Audio Communicator	\$330
		ZKMD472 -P (POE)	\$387
		ZKMD472-W (WiFi)	\$387

ZKSD330 High Speed Dome IP Camera		ZKSD330 * H.264 image compression * 1/4" SONY CCD * 480TVL resolution * IP66 * Motion detection * 18 X Optical / 12X Digital zoom * Motion detection * Webserver * 24V power supply included * External audio connections * Alarm contacts & RS 485 connectivity * Standard SD Card slot, supports max 32GB * PTZ support	\$2,400
		ZKSD330-W (WiFi)	\$2,457
ZKSD420 High Speed Dome IP Camera		ZKSD420 * H.264 image compression * 1/3" Super HAD CCD * 650TVL resolution * IP65 * Motion detection * 10 x Optical / 10 x Digital zoom * Webserver * External Audio Connection * Alarm contacts & RS 485 connectivity * 12V power supply included * Standard SD Card slot available, supports max 32G * PTZ support	\$1,130
		ZKSD420 - W (WiFi)	\$1,187
ZKSD422 High Speed Dome IP Camera		ZKSD422 * H.264 image compression * 1/3" Super HAD CCD * 650TVL resolution * Motion detection * 10 x Optical / 10 x Digital zoom * Webserver * External Audio Connection * Alarm contacts & RS 485 connectivity * IR distance:10-15m * 12V power supply included * Standard SD Card slot available, supports max 32G * PTZ support	\$1,190
		ZKSD420 - W (WiFi)	\$1,247
ZK-NV0401 4CH Embedded Network Video Recorder		ZK-NV0401 * 4-ch IP video input and 720P video recording at 25 fps * With VGA and CVBS * Supports playback while recording for 1 channel * H.264 compression * Support multi DDNS providers (Oray, 3322, dyndns) * Supports mouse to control PTZ connectivity * Supports 2TB Hard Disk, 1SATA Port * 12V power supply included	\$746
		ZK-NV0802 * 8-ch IP video input and 720P video recording at 25	

ZK-NV0802 8CH Embedded Network Video Recorder		<ul style="list-style-type: none"> * 8-ch IP video input and 720P video recording at 25 fps * HDMI, SPOT, VGA and CVBS ports * Supports playback while recording for 1 channel; * H.264 compression * Support multi DDNS (Oray, 3322, dyndns) * Supports mouse connectivity to control PTZ * Supports 4TB Hard Disk, 2SATA Port; * 12V power supply included 	\$1,440
ZKIP370 Standard Box IP Camera		ZKIP370 <ul style="list-style-type: none"> * H.264 image compression * 1/3" CMOS sensor * 1280*720 resolution and WDR * 4-9mm varifocal lens * Motion detection * Webserver * External audio connections * Alarm contacts & RS 485 Connectivity * 12V power supply included * Standard SD card slot, supports max 32GB 	\$450
		ZKMD370-P (POE)	\$507
		ZKMD370-W (WiFi)	\$507
		ACCESSORIES FOR ZKIP370	
ZKBR-001 Indoor Bracket		ZKBR-001 <ul style="list-style-type: none"> * Indoor bracket * Aluminum alloy * 60(L)*140(H)mm 	\$10
ZKBR-004 Outdoor Bracket		ZKBR-004 <ul style="list-style-type: none"> * Outdoor bracket * cast aluminum * 100(L)*85(H)*305(W)mm 	\$20
ZKHZ-02 Small outdoor camera enclosure		ZKHZ-02 <ul style="list-style-type: none"> * Outdoor enclosure * Aluminum alloy * 320(L)*135(H)*100(W)mm 	\$48
ZKHZ-03 Small outdoor enclosure with heater and fan		ZKHZ-03 <ul style="list-style-type: none"> * Outdoor enclosure * Aluminum alloy * 400(L)*135(H)*100(W)mm * Has a heater & fan 	\$92